

ABOX-U431C

4U Rack H310C Chipset Industrial Computer

Intel 6th/7th/8th/9th Core i7/i5/i3, Pentium, Celeron desktop processors

Specification

V1.0

Key features:

- Support Intel® 6th/7th/8th/9th Core™ i7/i5/i3, Pentium, Celeron Desktop multicore processors;
- Intel H310C industrial chipset, TDP=6W;
- 2* DDR4 U-DIMM, support 2666 Mhz, Max. up to 64GB;
- 3* SATA and 1* M.2 Storage slot;
- 2* GLAN, 4* USB3.2, 4* USB2.0, 6* COM, PS/2, 1* HDMI, 1* DVI;
- Front 2* USB design, Lockable front plate, Access protection;
- Max. support NVIDIA GeForce GTX3090 Graphic card.


Product Image



Technical Data

System	
CPU	Intel® 8 th /9 th Core™ i3/i5/i7, Pentium, Celeron Desktop LGA1151 CPUs, Max. TDP=95W
Chipset	Intel® H310C Chipset, TDP=6W
Memory	2 x DDR4 U-DIMM, 2400/2666 MHz, Dual channels, Max. up to 64GB
Storage	3 x 2.5" SATA3.0, 1x M.2
Display	1 x HDMI (Max. support resolution: 4096x2160, @ 30Hz) 1 x DVI-D (Max. support resolution: 1920x1200, @60Hz)
Network	2 x Intel® Ethernet Connection; LAN1: I211, LAN2: I219
Wireless	1 x Mini-PCIE (Optional support 3G/4G/LTE, Wi-Fi/BT expansion)
Audio	1 x Mic-in + 1 x Line-out (Realtek ALC 662)
USB	4 x USB 2.0 (Type-A), 4x USB3.2 (Type-A)
PS/2	1x PS/2
COM	2 x RS232/RS485/RS422 (COM1/COM2, DB9), 4x RS232 (COM3/4/5/6, jumper)
GPIO	Optional 16x GPIO
Expansion	1x PCIe 3.0 x16 slot 1x PCIe 2.0 x4 slot (Gen2 x4) 5x PCI slots (32-bit / 33 Mhz)
AI Computing	Max. support NVIDIA GeForce GTX3090 (PCIe 16x)
Power	AC Input, 110 ~ 240V, max. support power consumption 125W (Not include expansion card)
LED/Switch	1 x power button (including status LED light)
Watchdog	Programmable 255 seconds
OS	6 th Core™: Windows 7/8.1/10, 32/64 bits, Linux 7 th Core™: Windows 7/8.1/10, 64 bits, Linux 8 th /9 th Core™: Windows 10 64 bits, Linux
RAID	0, 1,5
Structure	
Material	SGCC
Treatment	Hard anodizing treatment
Color	Silver white
Cooling	PWM intelligent fan
Weight	14.18kg (Net weight)
Dimension	482.6mm(L) x 177mm(W) x 464.5mm(H)
Mounting	Desktop, 4U rack mount
Environmental	
Operation temp.	Operating temp.: -20~60°C (Industrial SSD)
Storage temp.	Storage temp.: -40~80°C
Humidity	10%~90%@40°C (non-condensation)
Vibration	SSD : 3Grms@5~500Hz , random , 1 hr/axis ;
Shock	10G/peak (11ms sec)

Dimension & Interface



Ordering Information

ABOX-U431C-xxxx	Intel LGA1151 xxxx Desktop CPUs, Intel H310C Chipset, 1*DVI-D, 1*HDMI, 2*RJ45, 4*USB3.2, 4*USB2.0, 2*COM, 1* P/S 2, AC 220V
Memory	DDR4 4G/8G/16G/32G/64GB
Storage	SSD: 32GB/64GB/128GB/256GB/512GB/1TB HDD: 500GB/1TB/2TB/4TB

Note: xxxx refer to 6th /7th /8th /9th Desktop CPUs Code



The information in this specification is subject to change without notice.

All parts of Mainkco IPC documentation are protected by copyright law and all rights are reserved. This documentation may not, in whole or in part, be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine-readable form without prior consent, in writing, from TAICENN Technology.