



CARACTERÍSTICAS PRINCIPALES

- ❑ Carcasa de aleación de aluminio sin ventilador.
- ❑ Compatible con 2 slot DDR5 máx. 64GB
- ❑ Wi-Fi doble banda con antenas externas (opcional).
- ❑ 8 puertos COM RS232/RS422/RS485.
- ❑ Compatible con SSD, HDD SATA 2,5" y M.2 2280 NVMe.
- ❑ Triple pantalla 2 HDMI (1.4) y 1 DP simultáneamente.
- ❑ Funcionamiento 24/7 Uso Industrial



SPECIFICATION	DESCRIPTION - IND9513
CPU	Intel Core i7-1355U 10-core 12threads up to 5Ghz 12MB Cache
TDP	15W-55W
Chipset	Intel SOC
BOIS	AMI BIOS, ACPI supported
Memory	2 x SO-DIMM DDR5 Slot Support 8GB/16GB/32GB/64GB DDR5 4800/5600Mhz
OS	Windows 10/11/ Linux
Audio	ALC662 chip Support 6 channels of sound
Network	Onboard 3* intel i226 Gigabit Ethernet NIC 10/100Mbps/1000Mbps BaseT LAN
Video	Intel Iris Xe Graphics G7. Triple display output synchronously
4G	Full hight 4G Module support. with SIM Card slot
Storage:	
SATA	1 x SATA3.0 slot for SATA HDD or SSD, support 6Gb/s
M.2	2 x M.2 2280 Nvme/SATA
Wi-Fi:	
Module	1 x M.2 NVME / 1x Minipcie for Wi-Fi module
Antenna	2 x inner RF cables and 2 x external antennas
Input/output port :	
Switch	1 x Power On/Off Switch
Power	1 x 12V DC In
PS2	1 x PS2
Gpio	1 x GPIO
USB	4 x USB2.0, 4 x USB3.0
Display	2 x HDMI 1.4 Output support 4K@30Hz
	1 DP
COM	8 x RS232/RS422/RS485 COM Port(COM1&2 Support RS485 only by BIOS Settings)
LAN	3 x i226 RJ45 Giga LAN
Audio	1 x MIC, 1 x SPK
Power and Working Environment:	
Input	DC100-240V AC/50-60Hz
Output	12V 10A
Operating Temperature	0/+60 Centigrade
Storage Temperature	-20/+ 70 Centigrade
Relative Humidity	0%~90% (non-condensing)
Product Dimension & Details:	
Functions	Calls on function automatically, Wake-On-LAN,PXE
Size	280*156*77mm
Weight	Net 2.5kg, Gross 3.5kg
Shell	Aluminum Alloy with Black color
Cooling Mode	Fanless
Package Content :	
Standard	1xMini PC, 1xPower Adapter, 1xPower Cord, 1xScrews Bag
Optional	Wi-Fi antennas, 1xHDMI cable, 1xUser Manual, 1xVESA mount & screws