

TW-133 Rugged Tablet 13.3" - Intel Core i7

T-BOX



MAIN FEATURES

- ❏ CPU Intel Core i7-1255U
- ❏ RAM 16GB, ROM 1TB M.2
- ❏ 13.3" 1080 x 1920 450nits Typ
- ❏ Dual-band WiFi and 4G LTE.
- ❏ USB 3.2 - Type-C - RS232
- ❏ HDMI - RJ45
- ❏ MIL-STD-810G - ISO-9001 - CE - FCC



SPECIFICATION	DESCRIPTION - TW133	
OS	Windows 11 pro	
CPU	I7-1255U, 10 cores, 12 threads/basic frequency 1.7GHz, turbo 4.7GHz/power consumption 15W	
GPU	Intel® Iris® Xe Graphics 96EU (I7)	
RAM/ROM	RAM : 16GB LPDDR5 / ROM: 1TB M.2 2242 SATA	
LCD	13.3 inch; 1080*1920; IPS, 450nits (TYP)	
Touch Screen	10 Point Touch, Support stylus included	
Camera	Front: 5MP; Rear: 8MP	
Power and Battery	8000mAh / voltage 7.6Vdc (60.80Wh)	
WWAN	4G Fre: FDD_LTE: B1/B2/B3/B4/B5/B7/B8/B28 WCDMA: B1/B2/B4/B5/B8	TDD_LTE: B40 GSM/EDGE: B2/B3/B5/B8
GPS	BDS, GPS, GLONASS	
WIFI	802.11a/b/g/n/ac/ax wireless internet Wireless AP (Mobile AP)2.4G, 5G; Support WIFI 6	
BLUETOOTH	5.2 Version	
NFC	13.56 MHz, Distance: 1-3cm, ISO14443 TYPE A	
MIC	Sensitivity: -32±2d ; Output Impedance: 2.2kΩx1	
SPEAKER	8Ω 1.5 Watt	
Sensor	1. Light , 2. Acceleration sensor & 3. Gravity sensor	
Size	330*205*19.5mm	
Weight	1450±50g	
Language	Multi language	
Interface In/Out Port	1. HDMI Type A*1 3. Type-c*1 (Supports fast charging) 5. Aviation interface x2: customized interface & RS232 (RS232 not fully functional, only TX RX GND) 7. Headphone Jack : 3.5mm Standard headphone interface 9. DC power interface : DC 4.0mm power interface	2. USB3.2*2 4. Anti-theft lock hole 6. Card slot: SIM card slot+TF card slot 8. Ethernet RJ45 : 10/100/1000M
Button	V+ -, Power, "F" for Barcode Scan	Customized Button: P, H (Default No Functionality)
1D/2D Barcode	Optional Honeywell N4680	
Accessories	1. Blue Box 3. Carry strap 5. Wrist strap	2. DC Charger (12V 4A) 4. Screw
Multi-Media (Hardware Decoding)	1. Photo Viewer: BMP, JPG, GIF, PNG 3. Audio Format: MP3,WMA,WAV,OGG,FLAC,ALAC, APE,AAC,AC-3,DTS (need license)	2. Video Format: MPEG 1/2/4,H.263/H.264, RMVB,WMV/VC-1,MVC,AVS,MJPEG. (UP TO 1080P)
Proof Degree	Anti-dust & Waterproof IP65	Dropping Resistance 1.2 meters
Certification	1. MIL-STD-810G 2. ISO-9001 3. CE, FCC, 3C	
Temperature	Storage Temperature: -25 °C to 80 °C	Operation Temperature: -20 °C to 55 °C
Keyboard	Optional Included	

Fecha de Actualización Junio 2025
Nota: Las especificaciones están sujetas a cambio sin notificación previa



www.terabox.cl



ventas@terabox.cl



